



## AC Adapter / Battery Charger / DC Inlet **ADCseries**

		ADC-13	ADC-18	ADC-19
Photo			and the second s	
Kind of power inlet		AC, External DC and battery charging		
AC power supply	Input	100V to 240V AC, 50Hz to 60Hz		
	Power cord	ACC-13~17	ACC-14 ~ 17	ACC-08 <b>~</b> 12
External DC power supply	Input	10V to 15V DC	10 to 15V DC	-
	Power cord	DCC-12 (Cigarette lighter plug), DCC-13 (Alligator clamps)		
Battery charging	Battery / Capacity	BTR-08 / 4.0Ah	BTR-09 / 4.0Ah	BTR-10 / 2.0Ah
	Charging voltage	13.2V	14.8V	14.8V
	Battery charge cord	DCC-14	DCC-18	-
High voltage protection circuit		Available (High input indicator equipped)	-	-
Use for		FSM-60S/60R, FSM-18S/18R	70S, 70R, 19S, 19R	12S, 12R
Usage		Power supply: Sloted into the above splicers Battery charging: Connecting to the battery as shown the photo below		Connecting to the above splicers externally
Dimensions(mm)		120W x 117D x 38H	132W x 117D x 38H	108W x 62D x 32H
Weight		340g	386g	273g
Battery charging		BTR-08 DCC-14 ADC-13	ADC-18	-

XAII models are Fujikura products.

Specifications and descriptions are subject to change without prior notice.